



Part Number: 2424DD

Enhanced Category 6 Nonbonded-Pair Cables

Product Description

CAT6+ (300MHz), 4-Pair, U/UTP Unshielded, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, LSZH Jacket

Technical Specifications

Use

Suitable Applications:	Horizontal and building backbone cable; Support current and future Category 6 and 5e applications, such as: 1000Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM
------------------------	---

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	No. of Pairs
Individual pair	24	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Element	Type	Material	Nominal Diameter
Individual pair	Dielectric	Polyethylene	1 mm

Color Chart

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

Outer Jacket Material

Material	Color	Nominal Diameter	Diameter +/- Tolerance	Ripcord
LSZH / FRNC	Blue, purple	5.5 mm	0.3 mm	Yes

Electrical Characteristics

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
93.8 Ohm/km	4 %	2 Ohm

Impedance

Nominal Characteristic Impedance

100 Ohm

Delay**Max. Delay Skew** **Nominal Velocity of Propagation (VP) [%]**

25 ns/100m

70 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2 dB/100m	75.3 dB	73.3 dB	73.3 dB	71.3 dB	70.8 dB	67.8 dB	20 dB	40 dB	35 dB
4 MHz	3.7 dB/100m	66.3 dB	64.3 dB	62.6 dB	60.6 dB	58.8 dB	55.8 dB	23 dB	40 dB	23 dB
10 MHz	5.8 dB/100m	61.8 dB	59.8 dB	56 dB	54 dB	50.8 dB	47.8 dB	25 dB	40 dB	15 dB
16 MHz	7.4 dB/100m	58.6 dB	56.6 dB	51.2 dB	49.2 dB	46.7 dB	43.7 dB	25 dB	38 dB	10.9 dB
20 MHz	8.3 dB/100m	57.1 dB	55.1 dB	48.8 dB	46.8 dB	44.8 dB	41.8 dB	25 dB	37 dB	9 dB
31.2 MHz	10.4 dB/100m	54 dB	52 dB	43.6 dB	41.6 dB	40.9 dB	37.9 dB	23.6 dB	35.1 dB	5.1 dB
62.5 MHz	15 dB/100m	49.1 dB	47.1 dB	34.1 dB	32.1 dB	34.9 dB	31.9 dB	21.5 dB	32.6 dB	
100 MHz	19.3 dB/100m	45.8 dB	43.8 dB	26.5 dB	24.5 dB	30.8 dB	27.8 dB	20.8 dB	30 dB	
200 MHz	28.3 dB/100m	40.9 dB	38.9 dB	12.6 dB	10.6 dB	22.8 dB	21.8 dB	19.5 dB	27 dB	
250 MHz	32.1 dB/100m	39.3 dB	37.3 dB	7.2 dB	5.2 dB	22.8 dB	19.8 dB	18 dB	26.5 dB	
300 MHz	35.6 dB/100m	38.1 dB	36.1 dB	2.5 dB	0.5 dB	21.3 dB	18.3 dB	17.5 dB		

High Freq Table Note: Limits below 4MHz are for information only.

Current**Max. Recommended Current [A]**

1.5 A

Voltage**Voltage Rating [V]**

72 V

Burning Load: 350 kJ/m

Applicable Standards & Environmental Programs

CPR Euroclass:	Dca-s2,d2,a1
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Patent:	http://www.belden.com/p

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
Data Category:	Category 6
ANSI Compliance:	ANSI/TIA/EIA 568-B.2-1 (2002)

Flame Test

ISO/IEC Flammability: IEC 60332-1

Mechanical Characteristics

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-20°C To +75°C
Bulk Cable Weight:	33 kg/km
Max Recommended Pulling Tension:	80 N
Min Bend Radius During Installation:	44 mm
Min Bend Radius During Operation:	22 mm

History

Revision Number: 1

Variants

Item #	Color
2424DD.06305	BLUE
2424DD.06A305	BLUE
2424DD.08A305	GRAY
2424DD.08500	GRAY

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.