



Part Number: 7965ELV

Category 6 Nonbonded-Pair Cables

Product Description

CAT6 (250MHz), 4-Pair, U/UTP Unshielded, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, LSZH Jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass B2ca
Suitable Applications:	Horizontal and building backbone cable; Support current and future Category 6 and 5e applications, such as: 1000Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4
Conductor Size:	23 AWG

Insulation

Type	Material	Nominal Diameter
Dielectric	Polyethylene	1 mm

Bonded-Pair:	No
--------------	----

Color Chart

Number	Color
Pair 1	White/Blue & Blue
Pair 2	White/Orange & Orange
Pair 3	White/Green & Green
Pair 4	White/Brown & Brown

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
LSZH / FRNC	6.6 mm	0.3 mm	1.15 mm

Construction and Dimensions

Min Elongation at Breakof Conductors:	10.0 %
Min Elongation at Breakof Insulation:	100.0 %
Min Elongation at Breakof Jacket:	100.0 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]
95 Ohm/km	4.0 %

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Impedance

Nominal Characteristic Impedance
100 Ohm

Delay

Max. Delay	Nominal Velocity of Propagation (VP) [%]
40 ns/100m	70 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	75.3 dB	72.3 dB	73.2 dB	70.2 dB	70.0 dB	67.0 dB	20 dB	40 dB	35 dB
4 MHz	3.8 dB/100m	66.3 dB	63.3 dB	62.4 dB	59.4 dB	58.0 dB	55.0 dB	23 dB	34 dB	23 dB
10 MHz	6.0 dB/100m	60.3 dB	57.3 dB	54.3 dB	51.3 dB	50.0 dB	47.0 dB	25 dB	30 dB	15 dB
16 MHz	7.6 dB/100m	57.2 dB	54.2 dB	49.6 dB	46.6 dB	45.9 dB	42.9 dB	25 dB	28 dB	10.9 dB
20 MHz	8.5 dB/100m	55.8 dB	52.8 dB	47.3 dB	44.3 dB	44.0 dB	41.0 dB	25 dB	27 dB	9 dB
31.2 MHz	10.7 dB/100m	52.9 dB	49.9 dB	42.1 dB	39.1 dB	40.1 dB	37.1 dB	23.6 dB	25 dB	5.1 dB
62.5 MHz	15.5 dB/100m	48.4 dB	45.4 dB	32.9 dB	29.9 dB	34.1 dB	31.1 dB	21.5 dB	22 dB	
100 MHz	19.9 dB/100m	45.3 dB	42.3 dB	25.4 dB	22.4 dB	30.0 dB	27.0 dB	20.1 dB	18. dB	
155 MHz	25.3 dB/100m	42.4 dB	39.4 dB	17.1 dB	14.1 dB	26.2 dB	23.2 dB	18.8 dB	17 dB	
200 MHz	29.1 dB/100m	40.8 dB	37.8 dB	11.6 dB	8.6 dB	24.0 dB	21.0 dB	18.0 dB	16 dB	
250 MHz	33.0 dB/100m	39.3 dB	36.3 dB	6.3 dB	3.3 dB	22.0 dB	19.0 dB	17.3 dB		

High Freq Table Note: Limits below 4MHz are for information only.

Coupling Attenuation Class: Type III

Segregation class according EN50174-2: a

Current

Max. Recommended Current [A]
1.5 A

Voltage

Voltage Rating [V]
72 V

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	52 kg/km
Max Recommended Pulling Tension:	80 N
Min Bend Radius During Installation:	52 mm
Min Bend Radius During Operation:	26 mm

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CPR Euroclass:	B2ca-s1a,d1,a1
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 6
ANSI Compliance:	ANSI/TIA/EIA 568-C.2 (2009)

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-3-25
-----------------------	----------------

Burning Load: 600 kJ/m

Part Number

Patent: <https://www.belden.com/resources/patents>

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.