

19" Wall-Mounting Cabinet 2-Part



Basic configuration:

- Sheet steel housing with welded frame
- With swing frame
- Completely pre-assembled, self-ventilated
- Pre-assembled for mounting of fan units in top and bottom
- Inside 2 x 19" profile rails front sided galvanised, depth-adjustable
- Front door with window made of certified safety glass
- Front door lockable with latch
- Internal earthing of all cabinet sections
- Cable infeed optionally from above or below, pre-punched openings
- Paint finish RAL7035 light grey powder-coated
- Degree of protection IP 20
- Supplied: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

Art.-No.	U	Height	Depth	Max. load	Weight
Depth 500 mm / Width 600 mm					
691604	4U	240 mm	500 mm	15.0 kg	15.5 kg
691606	6U	330 mm	500 mm	15.0 kg	19.0 kg
691609	9U	465 mm	500 mm	25.0 kg	22.0 kg
691612	12U	600 mm	500 mm	25.0 kg	26.0 kg
691615	15U	730 mm	500 mm	30.0 kg	30.0 kg
691618	18U	860 mm	500 mm	50.0 kg	33.5 kg
691621	21U	997 mm	500 mm	50.0 kg	37.5 kg
Depth 600 mm / Width 600 mm					
691604.1	4U	240 mm	600 mm	15.0 kg	20.5 kg
691606.1	6U	330 mm	600 mm	15.0 kg	24.0 kg
691609.1	9U	465 mm	600 mm	25.0 kg	27.0 kg
691612.1	12U	600 mm	600 mm	25.0 kg	31.0 kg
691615.1	15U	730 mm	600 mm	30.0 kg	35.0 kg
691618.1	18U	860 mm	600 mm	50.0 kg	38.5 kg
691621.1	21U	997 mm	600 mm	50.0 kg	42.5 kg

RoHS
compliant

Created MN	Date 11.05.10	19" Wall-Mounting Cabinet 2-part 6916XX / 6916XX.1	File: 6916XX(.1)_ENG
Last rev. MN	Date 11.05.10		